



Formosa Plastics®

Formolon® APURG

APURG Powder Purge Compound Series

The **APURG** compounds are highly filled, over stabilized dry-blends designed for use in PVC extruders. The material should be used for normal cleaning purposes prior to equipment shut down. It can also be used during short periods of down time due to maintenance (or other), remaining in the equipment for these short periods, providing a clean screw area for the equipment start up.

<u>Properties</u>	<u>Test Method</u>	<u>Typical Value</u>
Barbender heat stability @, 195C and 60 rpm	ASTM D-2538	>120 min

Effective as of November 2015

Any inquiries regarding this data sheet should be addressed to: 9 Peach Tree Hill Road • Livingston, NJ 07039 • Phone: (888) FPCUSA3 • Fax: (973) 422-7724

The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions concerning uses or applications are only the opinion of FORMOSA PLASTICS CORPORATION, U.S.A. and users should perform their own tests to determine the suitability of these products for their own particular purposes. However, because of numerous factors affecting the results, FORMOSA PLASTICS CORPORATION, U.S.A. MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, other than that the material conforms to the applicable current Standard Specifications Statements herein, therefore, should not be construed as representations or warranties. The responsibility of FORMOSA PLASTICS CORPORATION, U.S.A. for claims arising out of breach of warranty, negligence, strict liability or otherwise is limited to the purchase price of the material. Statements concerning the use of the products of formulations described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is assumed.

