



Formosa Plastics®

Caustic

25% Liquid Caustic Soda Specification - Membrane Grade

Items	Specification (by weight)	Test Method
Sodium Hydroxide (NaOH)	24-26% min.	ASTM E291
Sodium Chloride (NaCl)	200 wt ppm max.	IC Method
Sodium Carbonate (Na ₂ CO ₃)	0.15 wt % max.	ASTM E291
Sodium Sulfate (Na ₂ SO ₄)	80 wt ppm max.	IC Method
Sodium Chlorate (NaClO ₃)	100 wt ppm max.	IC Method
Iron (Fe)	3.0 wt ppm max.	ASTM E291

Date: August 1, 2007

Any inquiries regarding this data sheet should be addressed to: 9 Peach Tree Hill Road • Livingston, NJ 07039 • Phone: (888) FPCUSA3 • Fax: (973) 716-7230

The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions concerning uses or applications are only the opinion of FORMOSA PLASTICS CORPORATION, U.S.A. and users should perform their own tests to determine the suitability of these products for their own particular purposes. However, because of numerous factors affecting the results, FORMOSA PLASTICS CORPORATION, U.S.A. MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, other than that the material conforms to the applicable current Standard Specifications Statements herein, therefore, should not be construed as representations or warranties. The responsibility of FORMOSA PLASTICS CORPORATION, U.S.A. for claims arising out of breach of warranty, negligence, strict liability or otherwise is limited to the purchase price of the material. Statements concerning the use of the products of formulations described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is assumed.

Printed in the the USA on recycled paper

©Formosa Plastics Corporation, U.S.A.



ISO 9001:2000
FS 70459
FM 31429
FM 31430



ISO 14001
EMS 35710
EMS 36149

