



Formosa Plastics®

Caustic

50% Liquid Caustic Soda Product Specification

Membrane Grade

<u>ITEMS</u>	<u>SPECIFICATION</u>	<u>TYPICAL ANALYSIS</u>	<u>TEST METHOD</u>
Sodium Hydroxide (NaOH)	49.50 ~ 51.00 wt%	50.00 wt%	ASTM E291
Sodium Carbonate (Na ₂ CO ₃)	0.10 wt% Max	< 0.01%	ASTM E291
Sodium Oxide (Na ₂ O)	38.36 ~ 39.57 wt%	38.74 wt%	ASTM E291
Sodium Chloride (NaCl)	100 ppm Max	40 ~ 60 ppm	ASTM E1787
Sodium Chlorate (NaClO ₃)	50 ppm Max	10 ~ 30 ppm	ASTM E1787
Sodium Sulfate (Na ₂ SO ₄)	40 ppm Max	5 ~ 15 ppm	ASTM E1787
Iron (Fe)	3.0 ppm Max	2.0 ppm	ASTM E291

Revised 8/11/2010

Any inquiries regarding this data sheet should be addressed to: 9 Peach Tree Hill Road • Livingston, NJ 07039 • Phone: (888) FPCUSA3 • Fax: (973) 422-7723

The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions concerning uses or applications are only the opinion of FORMOSA PLASTICS CORPORATION, U.S.A. and users should perform their own tests to determine the suitability of these products for their own particular purposes. However, because of numerous factors affecting the results, FORMOSA PLASTICS CORPORATION, U.S.A. MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, other than that the material conforms to the applicable current Standard Specifications Statements herein, therefore, should not be construed as representations or warranties. The responsibility of FORMOSA PLASTICS CORPORATION, U.S.A. for claims arising out of breach of warranty, negligence, strict liability or otherwise is limited to the purchase price of the material. Statements concerning the use of the products of formulations described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is assumed.

© Formosa Plastics Corporation, U.S.A.



ISO 9001:2008
FS 70459
FM 31429



ISO 14001:2004
EMS 35710