



50% Liquid Caustic Soda Product Specification

Membrane Grade

<u>ITEMS</u>	<u>SPECIFICATION</u>	<u>TYPICAL ANALYSIS</u>	<u>TEST METHOD</u>
Sodium Hydroxide (NaOH)	49.50 ~ 51.00 wt%	50.00 %	ASTM E291
Sodium Carbonate (Na ₂ CO ₃)	0.10 wt% Max	< 0.01%	FTTC2418
Sodium Oxide (Na ₂ O)	38.36 ~ 39.57 wt%	38.74 %	ASTM E291
Sodium Chloride (NaCl)	100 wt ppm Max	40 ~ 60 ppm	ASTM E1787
Sodium Chlorate (NaClO ₃)	50 wt ppm Max	10 ~ 30 ppm	ASTM E1787
Sodium Sulfate (Na ₂ SO ₄)	40 wt ppm Max	5 ~ 15 ppm	ASTM E1787
Iron (Fe)	4.0 wt ppm Max	2.0 ppm	ASTM E291

Revised 05/18/2023

Any inquiries regarding this data sheet should be addressed to: 9 Peach Tree Hill Road • Livingston, NJ 07039 • Phone: (888) FPCUSA3

The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions concerning uses or applications are only the opinion of FORMOSA PLASTICS CORPORATION, U.S.A. and users should perform their own tests to determine the suitability of these products for their own particular purposes. However because of numerous factors affecting results, FORMOSA PLASTICS CORPORATION, U.S.A. MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, other than that the material conforms to the applicable current Standard Specifications Statements herein, therefore, should not be construed as representations or warranties. Statements concerning the use of the products of formulations described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is assumed.