



Formosa Plastics®

EDC

**EDC**

<u>ITEMS</u>	<u>SPECIFICATION</u>	<u>TYPICAL DATA</u>	<u>TEST METHOD</u>
Purity	99.9 wt% Min	> 99.95 wt%	FTTC 3301
Color	10 Alpha Max	5 Alpha	ASTM D1209
Water	50 wt ppm Max	25 ppm	ASTM E203
Acidity as Hydrochloric Acid	2 wt ppm Max	N.D.	FTTC 2505
Alkalinity as Sodium Hydroxide	2 wt ppm Max	N.D.	FTTC 2505
Iron	1 mg/L Max	N.D.	FTTC 2503
Total Low Boilers	450 wt ppm Max	< 100 ppm	FTTC 3301
Total High Boilers	450 wt ppm Max	< 150 ppm	FTTC 3301
Non-Volatile Residue	50 wt ppm Max	< 10 ppm	FTTC 2507

Revised 04/20/2023

Any inquiries regarding this data sheet should be addressed to: 9 Peach Tree Hill Road • Livingston, NJ 07039 • Phone: (888) FPCUSA3

The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions concerning uses or applications are only the opinion of FORMOSA PLASTICS CORPORATION, U.S.A. and users should perform their own tests to determine the suitability of these products for their own particular purposes. However because of numerous factors affecting results, FORMOSA PLASTICS CORPORATION, U.S.A. MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, other than that the material conforms to the applicable current Standard Specifications Statements herein, therefore, should not be construed as representations or warranties. Statements concerning the use of the products of formulations described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is assumed.

© Formosa Plastics Corporation, U.S.A.

Formolene® & Formolon® are registered trademarks of FPC USA