

Formolene[®] 1202K

Homopolymer for BOPP Film

Formolene[®] 1202K is a high molecular weight, polypropylene homopolymer designed for biaxially oriented film (BOPP). It has been designed for improved processability in the orientation process, which also results in better end use performance than existing grades. It does not contain slip or antiblock.

Formolene[®] 1202K meets the requirements of the U.S. Food and Drug Administration as specified in 21 CFR 177.1520, covering safe use of polyolefin articles and components of articles intended for direct food contact. For additional information on approved conditions of use for food contact applications, please refer to the "Products" section on our website (http://www.fpcusa.com/ourproducts.html).

This material is free of animal-derived content.

Typical Properties of this Commercial Grade

		Typical Values				
Property	Test Method	Eng	English		SI	
Melt Flow Rate, I ₂ @ 230°C	ASTM D1238	3	g/10min	3	g/10min	
Density	ASTM D1505	0.9	g/cm3	0.9	g/cm ³	
Tensile Strength at Yield (50 mm/min)	ASTM D638	5000	psi	34	MPa	
Elongation at Yield (50 mm/min)	ASTM D638	10	%	10	%	
Flexural Modulus (1.3 mm/min), 1% Secant	ASTM D790	200,000	psi	1379	MPa	
Rockwell Hardness	ASTM D785	104	R Scale	104	R Scale	
Notched Izod Impact Strength @ 73°F	ASTM D256A	0.5	ft-lb/in	27	J/m	

Note: Specimens were injection molded according to the conditions specified in ASTM D4101. Data for representative purposes only; not to be construed as product specification. Published 06/18

Any inquiries regarding this data sheet should be addressed to: 9 Peach Tree Hill Road • Livingston, NJ 07039 • Phone: (888) FPCUSA3 • Fax: (973) 422-7772

© Formosa Plastics Corporation, U.S.A.

The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions concerning uses or applications are only the opinion of FORMOSA PLASTICS CORPORATION, U.S.A. and users should perform their own tests to determine the suitability of these products for their own particular purposes. However, because of numerous factors affecting the results, FORMOSA PLASTICS CORPORATION, U.S.A. MAKES NO WARRANTY OF ANY KIND, EXPRESS OR INPLIED, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, other than that the material conforms to the applicable current Standard Specifications Statements herein, therefore, should not be construed as representations or warranties. The responsibility of FORMOSA PLASTICS CORPORATION, U.S.A. And the applicable current Standard Specifications Statements herein, therefore, should not be construed as representations or warranties. The responsibility of FORMOSA PLASTICS CORPORATION, U.S.A. For claims arising out of breach of warranty, required. The infinite material is the terminal. Statements concerning the use of the products of formulations described herein are not to be construed as recommending the infringement of any patent and no liability or infringement arising out of any such use is assumed.