

Formolene® 5144H

Homopolymer for Appliance Applications

Formolene® 5144H is a highly isotactic polypropylene homopolymer designed for consumer products and appliance applications requiring long-term heat-aging resistance and flexural endurance.

Formolene® 5144H has earned a UL continuous service rating of 65°C with recognition for typical use in laundry equipment.

This material is free of animal-derived content.

Typical Properties of this Commercial Grade

		Typical Values			
Property	Test Method	English		SI	
Melt Flow Rate, I ₂ @ 230°C	ASTM D1238	2.0	g/10 min	2.0	g/10 min
Density	ASTM D1505	0.9	g/cm³	0.9	g/cm³
Tensile Strength at Yield (50 mm/min)	ASTM D638	5,000	psi	34	MPa
Elongation at Yield (50 mm/min)	ASTM D638	10	%	10	%
Flexural Modulus (1.3 mm/min), 1% Secant	ASTM D790	210,000	psi	1448	MPa
Notched Izod Impact Strength @ 73°F	ASTM D256A	1.0	ft-lb/in	53	J/m
Heat Deflection Temperature @ 66 psi	ASTM D648	212	°F	100	°C

Note: Specimens were injection molded according to the conditions specified in ASTM D4101.

Data for representative purposes only; not to be construed as product specification. Published 5/05, Revised 3/18