

## Formolon® AW04

## Homopolymer/Compound

Formolon® AW04 is a NSF/ANSI Standard 14 certified medium molecular weight dry blend PVC compound. This compound has been engineered primarily for rigid extrusion applications. The exceptional stability properties provide a consistent whiteness that enhances the finish and marketability of the end product.

Suggested Applications: Pipe and Conduit

<b>Properties</b>	<b>Test Method</b>	Typical Value
Heat DeflectionTemp.(°F)	ASTM D648	169
Tensile Strength (PSI) Modulus (PSI	ASTM D638	7,200 410,000
Impact Strength (ft lbs/in)	ASTM D256	1.10

Effective as of November 2015

Any inquiries regarding this data sheet should be addressed to: 9 Peach Tree Hill Road • Livingston, NJ 07039 • Phone: (888) FPCUSA3 • Fax: (973) 422-7724

The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions concerning uses or applications are only the opinion of FORMOSA PLASTICS CORPORATION, U.S.A. and users should perform their own tests to determine the suitability of these products for their own particular purposes. However, because of numerous factors affecting the results, FORMOSA PLASTICS CORPORATION, U.S.A. MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDINO THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, other than that the material conforms to the applicable current Standard Specifications Statements herein, therefore, should not be construed as representations or warranties. The responsibility of FORMOSA PLASTICS CORPORATION, U.S.A. for claims arising out of breach of warranty, negligence, strict liability or otherwise is limited to the purchase price of the material. Statements concerning the use of the products of formulations described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is assumed.





